

"ALL STAINLESS" DIAPHRAGM SEAL PRESSURE GAUGE, TYPE PBS

TYPE	DRAWING	DIMENSIONS mm																																																			
01 02 03	<p style="text-align: center;">Flush Diaphragm</p>	<table border="1"> <thead> <tr> <th>DN</th> <th>PN bar</th> <th>d</th> <th>d1</th> <th>d2</th> <th>dM</th> <th>g</th> <th>x</th> <th>x1</th> <th>width</th> </tr> </thead> <tbody> <tr> <td>½"BSP</td> <td rowspan="6">600</td> <td>—</td> <td>18</td> <td>—</td> <td>16</td> <td>¼"BSP</td> <td>55</td> <td>20</td> <td>27</td> </tr> <tr> <td>¾"BSP</td> <td>32</td> <td>22</td> <td>—</td> <td>20</td> <td rowspan="3">½"BSP</td> <td>56</td> <td rowspan="2">21</td> <td>32</td> </tr> <tr> <td>1"BSP</td> <td>39</td> <td>29</td> <td>—</td> <td>28</td> <td>55</td> <td>41</td> </tr> <tr> <td>1½"BSP</td> <td>55</td> <td>44</td> <td>58</td> <td>38</td> <td>65</td> <td>50</td> </tr> <tr> <td>2"BSP</td> <td>68</td> <td>56</td> <td>78</td> <td>46</td> <td>70</td> <td>30</td> <td>65</td> </tr> </tbody> </table>	DN	PN bar	d	d1	d2	dM	g	x	x1	width	½"BSP	600	—	18	—	16	¼"BSP	55	20	27	¾"BSP	32	22	—	20	½"BSP	56	21	32	1"BSP	39	29	—	28	55	41	1½"BSP	55	44	58	38	65	50	2"BSP	68	56	78	46	70	30	65
	DN	PN bar	d	d1	d2	dM	g	x	x1	width																																											
	½"BSP	600	—	18	—	16	¼"BSP	55	20	27																																											
¾"BSP	32		22	—	20	½"BSP	56	21	32																																												
1"BSP	39		29	—	28		55		41																																												
1½"BSP	55		44	58	38		65	50																																													
2"BSP	68		56	78	46	70	30	65																																													
	<p style="text-align: center;">Flush Diaphragm</p>		<table border="1"> <thead> <tr> <th>DN</th> <th>PN bar</th> <th>d</th> <th>dM</th> <th>g</th> <th>x</th> <th>x1</th> <th>width</th> </tr> </thead> <tbody> <tr> <td>½"NPT</td> <td rowspan="6">600</td> <td rowspan="3">—</td> <td>16</td> <td>¼"BSP</td> <td>54</td> <td>19</td> <td rowspan="2">27</td> </tr> <tr> <td>¾"NPT</td> <td rowspan="2">24</td> <td rowspan="2">½"BSP</td> <td>60</td> <td>25</td> </tr> <tr> <td>1"NPT</td> <td>32</td> <td>65</td> <td>30</td> <td>41</td> </tr> <tr> <td>1½"NPT</td> <td>52</td> <td>32</td> <td>½"BSP</td> <td>65</td> <td>30</td> <td>46</td> </tr> <tr> <td>2"NPT</td> <td>78</td> <td>38</td> <td>—</td> <td>—</td> <td>30</td> <td>65</td> </tr> </tbody> </table>	DN	PN bar	d	dM	g	x	x1	width	½"NPT	600	—	16	¼"BSP	54	19	27	¾"NPT	24	½"BSP	60	25	1"NPT	32	65	30	41	1½"NPT	52	32	½"BSP	65	30	46	2"NPT	78	38	—	—	30	65										
DN	PN bar	d	dM	g	x	x1	width																																														
½"NPT	600	—	16	¼"BSP	54	19	27																																														
¾"NPT			24	½"BSP	60	25																																															
1"NPT					32	65	30	41																																													
1½"NPT		52	32	½"BSP	65	30	46																																														
2"NPT		78	38	—	—	30	65																																														
04 05		<p style="text-align: center;">Flush Diaphragm with female thread</p>	<table border="1"> <thead> <tr> <th>DN</th> <th>PN bar</th> <th>b</th> <th>d</th> <th>m</th> <th>dM</th> <th>g</th> <th>x</th> <th>x1</th> <th>HEX</th> </tr> </thead> <tbody> <tr> <td>1"BSP</td> <td rowspan="3">600</td> <td>49,5</td> <td>23,5</td> <td>28,5</td> <td>24</td> <td>¼"BSP</td> <td>30</td> <td rowspan="3">—</td> <td>41</td> </tr> <tr> <td>1½"BSP</td> <td rowspan="2">65</td> <td>30</td> <td>30,5</td> <td>28</td> <td rowspan="2">½"BSP</td> <td rowspan="2">30</td> <td>50</td> </tr> <tr> <td>2"BSP</td> <td>40</td> <td>35</td> <td>46</td> <td>70</td> </tr> </tbody> </table>	DN	PN bar	b	d	m	dM	g	x	x1	HEX	1"BSP	600	49,5	23,5	28,5	24	¼"BSP	30	—	41	1½"BSP	65	30	30,5	28	½"BSP	30	50	2"BSP	40	35	46	70																	
DN	PN bar	b	d	m	dM	g	x	x1	HEX																																												
1"BSP	600	49,5	23,5	28,5	24	¼"BSP	30	—	41																																												
1½"BSP		65	30	30,5	28	½"BSP	30		50																																												
2"BSP			40	35	46				70																																												