

GHM GROUP - Martens | GHM Messtechnik GmbH
Kiebitzhörn 18 | 22885 Barsbüttel | GERMANY
Phone +49 40 67073-0 | Fax +49 40 67073-288
www.ghm-group.de | info@ghm-group.de



Product information

**Potentiometric level meter
MLP433-OR**



- Continuous level measurement
- Suitable for metallic tanks and containers
- Process connection **GHMadapt G 1/2"** hygienic
- Flexible installation, compact version
- No moving parts in the measured fluid
- 2 switching outputs, analogue output
- Wide view LED status display
- Parameterisation with **GHMware** via USB interface

Technical data

Power supply

Supply voltage : 18..30 V DC, max. 130 mA
Electrical connection : M12 plug connector or cable gland M16x1,5
Polyamide (PA) or stainless steel (1.4305)
CE conformity : EN 61326-1:2013

Ambient conditions

Ambient temperature : -20..+60 °C
Climate class : EN 60068-2-38:2009
Vibrations : EN 60068-2-6:2008, GL Test 2

Sensor

Probe tube length : 100..999 mm (Ø 6 mm),
(Measuring range) 1000..2500 mm (Ø 10 mm)
Process temperature : -20..+100 °C, 140 °C < 30 min.
CIP- / SIP capable

Process pressure : -1..10 bar
Process material : 1.4404, PEEK, FDA compliant
Process connection : G 1/2" hygienic
Torque : 5..10 Nm

Min. media conductivity : 1µS < 20 µS, ≥ 20µS
Measuring accuracy : < 3% < 0.5 % of measuring range
Linearity : < 2% < 0.3 % of measuring range

Output


Analogue output : Active, 0/4..20 mA, Resistance < 600 Ω
Damping : Programmable from 0.05..10 s
Switching outputs : Transistor PNP / NPN programmable, max. 30 V / 100 mA

Response time : Programmable from 0.01..10 s
Galvanic isolation : Sensor, power supply/outputs
LED status message : 3 colours, programmable


Housing
Material : 1.4305
LED viewing window : Acrylic glass (PMMA)
Protection class : IP67 / IP69K

Accessories	
ACI211	USB connection cable
APH process adaptation, ACH connection lines see separate product information GHMadapt / Accessories	

Dimensions



Wiring



Cable colours M12 plug: 1 = brown, 2 = white, 3 = blue, 4 = black, 5 = grey

Order code

MLP433 - **OR** - - - - - - - - -

1. Type	OR	Without reference electrode
2. Process connection	2	G1/2" hygienic
3. Probe tube material	0	stainless steel (316L) 1.4404
	1	stainless steel (316L) 1.4435
4. Probe tube diameter	06	6 mm
	10	10 mm
5. Immersion length (length specification to 1 mm)	0100..0500	100 to 500 mm
	0501..0999	501 to 999 mm
	0500..1500	500 to 1500 mm
	1501..2500	1501 to 2500 mm
6. Probe tube insulation	0	without insulation
	1	with PFA-insulation (For installation from top)
7. Electrical connection	0	M12-plug (standard)
	1	cable gland M16x1.5; polyamide (PA)
	2	cable gland M16x1,5; stainless steel (1.4305)
8. Options	00	without option
9. Certificate according to DIN EN 10204. Please specify only if required.	WZ2.2	certificate of conformity 2.2

Subject to technical changes