

3-PIN. PROBE FOR LEVEL CONTROL (CONDUCTIVE)

**GNS-3P**

Art. no. 603170

3-pin. level probe

General:

- For all industrial applications
- Alarm-, Level- and Doseregulation
- Optional teflon covered staffs
- Combined with control electronics (ALSCHU 300, ALSCHU 485 OE / 3P or MINAL) an accurate liquids level control system

Specifications:

| | |
|-------------------------------|--|
| Number of electrodes: | 3 pieces |
| Length of electrodes: | 150 mm, other lengths upon request, probes can be cutted to needed length, in order to be adapted to local conditions. |
| Electrical connection: | 2 m cable |
| Switching distance: | 10 mm |
| Dimensions: | |
| Electrode length: | 150 mm |
| Electrode diameter: | 3 mm |
| Electronics box: | 55 x 35 mm (W x H) |
| Scope of supply: | Device, manual |

Option:**other length available****Teflon covered staffs**

only tip is uncovered (for electrodes used in salt water, ...)

Suitable for:

Alschu 300 FG, Alschu 300 SP, ALSCHU 485 OE / 3P

3-PIN. PROBE FOR LEVEL CONTROL (CONDUCTIVE)

**GNS-3P-SLV**

Art. no. 604786

3 electrodes with Poliolefin coating

- cooling water
- all conductive liquids

GNS-3P-SLK

Art. no. 604016

3 electrodes with Kynar coating

- food and beverage industry
- chemical industry

GNS-3P-SLE

Art. no. 603172

3 electrodes with PTFE coating


- aggressive conductive liquids

General:

- Coated electrodes
- Rugged construction, sealed
- Alarm or level regulation or dosage of liquids
- Combined with control electronics (ALSCHU 300, ALSCHU 485 OE / 3P) an accurate liquids level control system

Specifications:

| | |
|-------------------------------|--|
| Number of electrodes: | 3 pieces |
| Length of electrodes: | 500 mm, other lengths upon request, probes can be cutted to needed length, in order to be adapted to local conditions. |
| Electrical connection: | elbow-type plug acc. to EN 175301-803/A |
| Process connection: | G 1", Polypropylen |
| Pressure max.: | 6 bar |
| Temperature max.: | +100 °C |
| Protection rating: | IP65 |
| Dimensions: | SW: 40 mm A: 68 mm B: 20 mm L: 500 mm |

**Scope of supply:** Device, manual**Suitable for:**

Alschu 300 FG, Alschu 300 SP, ALSCHU 485 OE / 3P